Three USB-C Power Delivery ports and one USB-A QC 3.0 port.



Charge four devices



Compatibility



100 W
From one USB-C port

3 + 1
USB-C PD and USB-A QC ports

190 g
Charger weight

Product details



PPS charging

Voltage and current adjust in real time.



Built-in protection

Overcurrent, overvoltage, overtemperature and overload protection.



Compact design

85.2 × 93.8 × 30.2 mm.

PRODUCT IDENTIFICATION

SKU EW1336

EAN 8052101435665

Product page

Technical specifications

USB-C1 / C2 / C3 output	5 V / 3 A; 9 V / 3 A; 12 V / 3 A; 15 V / 3 A; 20 V / 5 A (100 W max., PD 3.0 / QC 4+)
USB-A output	5 V / 3 A; 9 V / 3 A; 12 V / 2.5 A (QC 3.0)
AC input	110-240 V, 2 A max.
USB-C protocols	PD 3.0, QC 3.0/3+/4.0/5.0, PPS, BC 1.2, Apple 2.4 A, DCP, AFC, FCP and SCP
USB-A protocols	QC 3.0
Input connector	CEE 7/16 (Euro) male
Protection	overcurrent, overvoltage, overtemperature and overload
Material	ABS + PC, glossy and matt finish
Colour	black
Dimensions	85.2 × 93.8 × 30.2 mm
Weight	190 g

Power distribution

Port combination	Power per port or group
USB-C1 + USB-C2	65 W + 35 W
USB-C1 + USB-C3	65 W + 35 W
USB-C1 + USB-A	65 W + 30 W
USB-C2 + USB-C3	65 W + 35 W
USB-C2 + USB-A	65 W + 30 W
USB-C3 + USB-A	12 W + 12 W
USB-C1 + USB-C2 + USB-C3	45 W + 35 W + 20 W
USB-C1 + USB-C2 + USB-A	45 W + 35 W + 18 W
USB-C1 + (USB-C3 + USB-A)	65 W + 24 W shared by USB-C3/USB-A
USB-C2 + (USB-C3 + USB-A)	65 W + 24 W shared by USB-C3/USB-A
USB-C1 + USB-C2 + (USB-C3 + USB-A)	45 W + 35 W + 15 W shared by USB-C3/USB-A

Package and documentation



Package contents

EW1336 charger and quick guide

Multilingual quick guide

EU declaration of conformity

Manufacturer datasheet

Specifications and images from the CORA Shopify export. Documents published by Ewent.