TECHNICAL DATASHEET

EW5625 – Glue repositionable 400ml

1. Sector of application

Any sector that needs gluing operations.

2. Description

Repositionable rapid adhesive based on modified elastomers and terpene resins. It glues light materials: plastics, paper, corks, cardboard, expanded polystyrene, textiles, foams. Shake well before the use. Clean the surfaces to be glued.

3. Technical features

forms:	aerosol
colours:	straw yellow
flash point:	extremely flammable
densità spray:	0.712 kg/l +/- 0,05
propellente:	buthane/propane
packaging:	400ml x 12pz
storages:	cool and airy premises place. The range of temperature from +10°C to +30°C; avoid the accumulation of electrostatic charge .
deadline	3 years from production

4. Use

Shake the bottle before use. Spray the products about 20 cm away directly on the interested parts keeping the cylinder in vertical position. Leave to act for a few moments before joining the surfaces to be glued. Apply in the quantities strictly necessary in order to avoid dripping and product waste. To avoid clogging of the nozze, after use it s advisable to turn the cylinder upside down and dispense until the spray jet no longer shows traces of adhesive.
Read and observe the safety warnings on the label. For information on handling, transport refer to the safety data sheet. This informations are relative to product's property reffered on the date of compilation indicated above.